

Valves

	NOMINAL	BSP	REC. FLOAT	CARTON	RRP (Each)	TRADE (Each)	TRADE (Each)
PRODUCT NO.	SIZE	SIZE	SIZE	QUANTITY	Incl GST	Excl GST	Incl GST

120 SERIES PLASTIC SLEEVE VALVE (DUAL ACTION)

91 4704 10	32	1-1/4"		20			
------------	----	--------	--	----	--	--	--

100 SERIES PLASTIC HORIZONTAL VALVE

90 3002 00	15	1/2"		50			
90 3003 00	15	1/2"		50			
90 3004 00	15	1/2"		50			

STAINLESS STEEL 316 FLOAT VALVES

90 3991 00	15	1/2"	125				
90 3992 00	20	3/4"	125				
90 3993 00	25	1"	125				
90 3995 00	40	1 1/2"	200				

CISTERN VALVE

91 1527 00	15	1/2"		50			
------------	----	------	--	----	--	--	--

	NOMINAL	BSP	REC. FLOAT	CARTON	RRP (Each)	TRADE (Each)	TRADE (Each)
PRODUCT NO.	SIZE	SIZE	SIZE	QUANTITY	Incl GST	Excl GST	Incl GST

SERVO TANK FILLING VALVES (Includes Lever)

90 3815 00	40	1 1/2"	255				
90 3816 00	50	2"	255				
90 3817 00	80	3"	255				

	CONNECTION	CARTON	RRP (Each)	TRADE (Each)	TRADE (Each)
PRODUCT NO.	DESCRIPTION	TYPE	QUANTITY	Incl GST	Incl GST

STOCK PROOF TROUGH VALVE

AQ100B	Brass Valve with Float	3/4"	15		
AQ200B	Brass Valve with Float	1"	15		
AQ300B	Brass Valve with Float	1 1/4"	15		
AQ400P	Plastic Valve with Float	3/4"	15		
AQ500P	Plastic Valve with Float	1"	15		
AQ600P	Plastic Valve with Float	1 1/4"	20		
AQ900	Float & Poly Tube Only		20		



For more details on the recommended float sizes and lever lengths please refer to page 97

★ Indicates the product is not a stock item, and will be ordered in by request
 Product codes without a symbol indicates the product is available as a stock item from the local Philmac branch.
 Note that this is to be treated as a *guide* only, and stock status may differ between Philmac state distribution centres in line with local market preferences.



150 SERIES BRASS VALVES & 100 SERIES PLASTIC VALVES & STAINLESS STEEL 316 VALVES

Product Number	Body Material	Inlet Size	Thread Type ¹	Lever Length	Lever Thread	Recommended Float Size ²	
						AS1910 ³	Agricultural ⁴
90300500	Brass	3/8" BSP	Short parallel (15 mm)	125 mm	5/16" BSW	4" (100)	4" (100)
90300700	Brass	1/2" BSP	Tapered	200 mm	5/16" BSW	4" (100)	4"(100)
90301300	Brass	1/2" BSP	Long parallel (38 mm)	250 mm	5/16" BSW	4" (100)	4"(100)
90301500	Brass	1/2" BSP	Long parallel (38 mm)	200 mm	5/16" BSW	4" (100)	4"(100)
90302300	Brass	1/2" BSP	Long parallel (38 mm)	200 mm	5/16" BSW	4" (100)	4"(100)
90303100	Brass	1/2" BSP	Short parallel (25 mm)	200 mm	5/16" BSW	4" (100)	4"(100)
90304400	Brass	3/4" BSP	Tapered	250 mm	5/16" BSW	6" (150)	6" (150)
90304600	Brass	1" BSP	Tapered	355 mm	5/16" BSW	6" (150)	6" (150)
90304800	Brass	1-1/4" BSP	Tapered	355 mm	3/8" BSW	8" (200)	8" (200)
90304900	Brass	1-1/2" BSP	Tapered	425 mm	3/8" BSW	8" (200)	8" (200)
90305000	Brass	2"	Tapered	455 mm	1/2" BSW	10" (255) ⁵ CU	9" (225)
90300200	Plastic	1/2" BSP	Long parallel	250 mm	5/16" BSW	4" (100)	4" (100)
90300300	Plastic	1/2" BSP	Long parallel	200 mm	5/16" BSW	4" (100)	4" (100)
90300400	Plastic	1/2" BSP	Long parallel	125 mm	5/16" BSW	-	4" (100)
90399100	Stainless	1/2" BSP	Tapered	255 mm	5/16" BSW	5" (125) SS	-
90399200	Stainless	3/4" BSP	Tapered	255 mm	5/16" BSW	5" (125) SS	-
90399300	Stainless	1" BSP	Tapered	355 mm	5/16" BSW	5" (125) SS	-
90399500	Stainless	1-1/2" BSP	Tapered	405 mm	3/8" BSW	8" (200) SS	-

120 SERIES PLASTIC VALVES (SLEEVE VALVES) & CISTERN VALVE

Product Number	Inlet Size	Thread Type	Lever Length	Lever Thread	Recommended Float Size ²
91470320	3/4 & 1" BSP	Tapered	300 mm	5/16" BSW	6" (150)
91470201	3/4" BSP	Long parallel	300 mm	5/16" BSW	6" (150)
91470211	3/4" BSP	Long parallel	170 mm	5/16" BSW	6" (150)
91470301	1" BSP	Long parallel	300 mm	5/16" BSW	6" (150)
91470311	1" BSP	Long parallel	170 mm	5/16" BSW	6" (150)
91470400	1-1/4" BSP	Tapered	400 mm	5/16" BSW	6" (150) x 2
91470410	1-1/4" BSP	Tapered	440 mm	5/16" BSW	6" (150) x 2
91152700	1/2" BSP	Short parallel	355 mm	5/16" BSW	4" (100)

100 SERIES PLASTIC VALVES

Product Number	Inlet Size	Thread Type ¹	Lever Length	Lever Thread	Recommended Float Size ²	
					AS1910 ³	Agricultural ⁴
90300200	1/2" BSP	Long parallel	250 mm	5/16" BSW	4" (100)	4" (100)
90300300	1/2" BSP	Long parallel	200 mm	5/16" BSW	4" (100)	4"(100)
90300400	1/2" BSP	Long parallel	125 mm	5/16" BSW	-	4"(100)

1. All parallel threads have a body back nut fitted except the 90300500 (3/8"). The 90302300 also has a stem sleeve fitted
2. Recommended floats are plastic unless designated otherwise. CU = copper. SS = stainless steel
3. To comply with AS1910 valves the recommended float size provides a shut-off pressure of 1400 kPa
4. For agricultural purposes the recommended float size achieves at least a shut-off pressure of 1250 kPa
5. Uses copper float 90162300

AS 1910: WATER SUPPLY - Float control valves for use in hot and cold water.